

1. Producer / supplier



	Quadrant EPP Belgium NV I.P. Noord – R. Tavernierlaan 2 B – 8700 Tielt Tel.: +32/(0)51/42 35 11 Fax: +32/(0)51/42 33 00		
2. Product description			
Commercial product name:	ERTACETAL [®] C		
These products are 'articles' ac	These products are 'articles' according to the Regulation (EC) No 1907/2006 (REACH).		
Material characterization:	Polyacetal copolymer [POM-C]		
3. Product characteristics			
Form:	semi-finished products (round rods, sheets, plate machined from semi-finished products	s, tubes) / finished parts	
Colour:	natural (white) / black / colours	Test methods	
Odour:	odourless	rest methous	
Density:	1.41 g/cm³	ISO 1183-1	
Melting temperature:	165 °C	ISO 11357-1/-3	
Glass transition temperature:	Values for this property are only given here for amorphous mate	ISO 11357-1/-2 erials and not for semi-crystalline ones.	
Thermal decomposition:	> 230 °C		
Self ignition temperature:	> 340 °C	ASTM D 1929	
Solubility in water:	insoluble		
4. Handling and storage			
Machining:	During machining of the semi-finished products, e slipping or tripping hazard and observe the maxin dust and formaldehyde levels on the workplace w Wear safety goggles during machining.	num allowable concentration of	
Storage:	The products shall be stored indoors in a normal 30 - 70% RH) and kept away from any source of UV-lamps, chemicals (direct or indirect contact), i Dimensional changes (camber, warpage, shrinka as slight colour shifts of the external surfaces can does generally not pose a problem in case of sen surface-layer is mostly removed anyway upon maparts.	degradation such as sunlight, onising radiation, flames, etc. ge) of the products as well occur with time. The latter ni-finished products since the	
Safety measures:	Standard industrial safety recommendations shall be observed. Temperatures above the melting temperature shall be avoided.		

Please also note the disclaimer on page 3 of this document.

Quadrant Engineering Plastic Products global leader in engineering plastics for machining www.quadrantplastics.com 1/3

ERTACETAL[®] C

5. Fire-fighting measures



PRODUCT HANDLING INFORMATION SHEET

	Suitable extinguishing media:	Water, foam, dry chemical, CO ₂ . Adapted to the nature and extend of fire.	
	Hazardous decomposition pro-	The main products formed in case of overheating and combustion are carbon monoxide, carbon dioxide and formaldehyde. Formation of further hazardous decomposition products depends upon the fire conditions and can not be excluded. Firemen should wear self-contained breathing apparatus and protective clothing	
		to prevent contact with skin and/or eyes. If exposed to combustion fumes in a high concentration, bring the victim into fresh air. If molten material contacts skin, cool rapidly with cold water and obtain medical attention for removal of adhering material and treatment of the burn.	
6.	Disposal considerations		
	products is not classified as haza Waste disposal:	 bite Catalogue and Hazardous Waste List', uncontaminated waste from the indous. The following six-digit codes can be used: 07 02 13 waste plastic from the manufacture, formulation, supply and use of plastics 12 01 05 plastic shavings and turnings 16 01 19 plastic, from end-of-life_vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance 17 02 03 plastics from municipal wastes (household waste and similar commercial, industrial and institutional wastes) When recycling is not feasible, waste disposal by incineration or landfill can be applied. Disposal methods shall conform to local or other government regulations. The products do not contain cadmium pigments or cadmium stabilisers. They are not biologically degradable, but based on the present state of knowledge no negative effects on the environment may be anticipated. 	
7. Marking and transport information			
	Classification and labelling:	Hazard warning labelling in accordance with relevant EC-Directives is not required.	
	International transport regulati	ons: Not applicable	
8.	Other information		
	programme, machining instructio	the latest information on the Quadrant products (product data sheets, delivery ns, chemical resistance, regulatory information) as well as for our statements	

ERTACETAL[®] is a registered trademark of the **Quadrant Group**.

concerning the European Regulation (EC) No 1907/2006 (REACH).

Please also note the disclaimer on page 3 of this document.



This brochure and any data and specifications presented on our website shall provide promotional and general information about the Engineering Plastic Products (the "Products") manufactured and offered by Quadrant Engineering Plastic Products ("Quadrant") and shall serve as a preliminary guide. All data and descriptions relating to the Products are of an indicative nature only. Neither this brochure nor any data and specifications presented on our website shall create or be implied to create any legal or contractual obligation.

Any illustration of the possible fields of application of the Products shall merely demonstrate the potential of these Products, but any such description does not constitute any kind of covenant whatsoever. Irrespective of any tests that Quadrant may have carried out with respect to any Product, Quadrant does not possess expertise in evaluating the suitability of its materials or Products for use in specific applications or products manufactured or offered by the customer respectively. The choice of the most suitable plastics material depends on available chemical resistance data and practical experience, but often preliminary testing of the finished plastics part under actual service conditions (right chemical, concentration, temperature and contact time, as well as other conditions) is required to assess its final suitability for the given application. It thus re-mains the customer's sole responsibility to test and assess the suitability and compatibility of Quadrant's Products for its intended applications, processes and uses, and to choose those Products which according to its assessment meet the requirements applicable to the specific use of the finished product. The customer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, or any consequence thereof, and shall verify its quality and other properties.

3/3