

EVERFLEX PVC SOLVENT CLEANER

DESCRIPTION

EVERFLEX PVC SOLVENT CLEANER is a fast acting, non smear formulation suitable for removing ingrained dirt and marks on all PVC frames, trim and cladding. May also be used on plastic garden furniture*

BENEFITS

- * Fast drying
- * Removes ingrained dirt.

AREAS FOR USE

- * Cleaning all PVC window frames, trim etc and most plastic garden furniture.

LIMITATIONS

- * Extremely dirty surfaces may require a second application.
- * Always use a separate cloth for spreading and buffing
- * The quality of plastic used for garden furniture does vary dramatically. Always test a small inconspicuous area prior to use to ensure compatibility/colour fastness.

APPLICATION

Always read health and safety information before applying this product.

Apply and spread with a soft cloth, working well into the surface. Leave for 15 minutes and buff with a separate dry soft cloth.

SPECIFIC DATA

APPEARANCE:	liquid	VOLATILE CONTENT:	Not given
COLOUR:	Colourless	AUTO IGN:	N/D
ODOUR:	Camphor.	EXPLOSION LIMITS:	Not given
MELTING POINT:	Not det.	DENSITY:	0.85g/cm ³
FLASHPOINT:	<21°C (CC)	pH:	N/A
SOLUBILITY:	Slightly soluble in water.	VISCOSITY:	-

HEALTH AND SAFETY

LABEL FOR SUPPLY: HIGHLY FLAMMABLE (F+)
HARMFUL (Xn)

RISK PHRASES R11 - Highly Flammable.
R65 - Harmful: may cause lung damage if swallowed.
R36/38 - Irritating to eyes and skin.

SAFETY PHRASES: S2 - Keep out of reach of children.
S24/25 - Avoid contact with skin and eyes.
S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37 - Wear suitable gloves.
S46 - If swallowed, seek medical advice and show this container label.
S51 - Use only in well-ventilated areas.

STORAGE

Store in cool dry conditions between + 5°C and 25°C. Avoid heat and static discharges.

SHELF LIFE

Use within 2 years.

SAFETY DATA SHEET

PVCU SOLVENT CLEANER

Page 1

Issued: 10/04/2003

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PVCU SOLVENT CLEANER

Product code: PVCS1

Use / description of product: Highly flammable or extremely flammable. Harmful.

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9 0SW

ENGLAND

Tel: +44 (0) 113 240 3456

Fax: +44 (0) 113 200 9418

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: 4-METHYLPENTAN-2-ONE 30-50%

CAS: 108-10-1

EINECS: 203-550-1

[F] R11; [Xn] R20; [Xi] R36/37; [Xi] R66

- LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),
HYDROTREATED HEAVY 10-30%

CAS: 64742-48-9

EINECS: 265-150-3

[-] R10; [Xn] R65; [Xi] R66

- 2-BUTOXYETHANOL 30-50%

CAS: 111-76-2

EINECS: 203-905-0

[Xn] R20/21/22; [Xi] R36/38

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes, respiratory system and skin. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

SAFETY DATA SHEET

PVCU SOLVENT CLEANER

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients: 4-METHYLPENTAN-2-ONE

TWA (8 hr exposure limit): 208 mg/m³ STEL (15 min exposure limit): 416 mg/m³ (OES)

- 2-BUTOXYETHANOL

TWA (8 hr exposure limit): 25 ppm STEL (15 min exposure limit): 50 ppm (OES)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Sweet-smelling

Viscosity: Non-viscous

Boiling point/range°C: 115

Flash point°C: -18

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Ingredients: 4-METHYLPENTAN-2-ONE

IPR RAT LD50 400 mg/kg

ORL MUS LD50 1900 mg/kg

ORL RAT LD50 2080 mg/kg

- 2-BUTOXYETHANOL

IVN RAT LD50 307 mg/kg

ORL MUS LD50 1230 mg/kg

ORL RAT LD50 470 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1993

ADR Class: 3

Packing group: II

Classification code: F1

Shipping name: FLAMMABLE LIQUID, N.O.S.

Labelling: 3

Hazard ID no: 33

**IMDG / IMO**

UN no: 1993

Class: 3

Packing group: II

EmS: 3-07/

Marine pollutant: .

Labelling: 3

IATA / ICAO

UN no: 1993

Class: 3

Packing group: II

Packing instructions: 305(P&CA); 307(PAO)

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Harmful.



Risk phrases: R11: Highly flammable.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

PVCU SOLVENT CLEANER

Safety phrases: S2: Keep out of the reach of children.
S7: Keep container tightly closed.
S13: Keep away from food, drink and animal feeding stuffs.
S16: Keep away from sources of ignition - No smoking.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S46: If swallowed, seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R11: Highly flammable.
R20: Harmful by inhalation.
R36/37: Irritating to eyes and respiratory system.
R66: Repeated exposure may cause skin dryness or cracking.
R10: Flammable.
R65: Harmful: may cause lung damage if swallowed.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.