

EVERBUILD ONE STRIKE FILLER

DESCRIPTION

EVERBUILD ONE STRIKE is a revolutionary ready-mixed lightweight filler for the preparation of numerous surfaces prior to painting or wallpapering. Based on high strength lightweight polymeric fillers, the product outperforms conventional fillers in most applications. Designed for professional and D.I.Y use.

BENEFITS

- Fills in one go- No need to build up layers of filler - fills up to 75mm deep in one application.
- Easy to use - lightweight paste is incredibly easy to apply.
- No sanding required - finishes to a smooth surface.
- No sagging - the lightweight properties of ONE STRIKE prevent sagging even on ceilings.
- Non-shrink - will not shrink back whilst drying.
- Quick drying - ready to paint/paper in just 30 minutes.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable
- Internal/external use.
- Dries brilliant white.

AREAS FOR USE

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

LIMITATIONS

- Do not use to fill plastic or metals.
- Do not apply when rain is imminent (external use)
- Do not apply in temperatures (ambient and surface) below 5°C.

SURFACE PREPARATION

All surfaces must be clean, dry, free from dust, grease and other contamination.

APPLICATION

Apply direct from tub with spatula/spreader. Smooth over surface and allow to dry. Sanding is not normally required although the product may be sanded if required.

SPECIFIC DATA

APPEARANCE:	Lightweight brilliant white paste.
S.G (20°C):	0.35gcm ³ (approx)
MOVEMENT ACCOM.	Low/moderate
MAXIMUM FILL	75mm in one coat -further layers may be built up
MAXIMUM WIDTH	50mm
APPLICATION TEMP.	5°C to 30°C.
DRYING TIME	30 minutes at 20°C 50% R.H.
pH	8.0-9.0
SOLIDS CONTENT	63% w/w.

HEALTH AND SAFETY

Safe in normal use. Avoid inhalation of dust once dry. Do not eat or drink during use. Remove product with soap and water. If product enters eyes, rinse immediately with cold water and seek medical attention if irritation persists. If ingested, give plenty of water to drink and seek medical attention. See separate 16 point data sheet for full assessment.

STORAGE

Store at moderate temperatures.

SHELF LIFE

12 months when stored according to manufacturers instructions.

SAFETY DATA SHEET

ONE STRIKE FILLER

Page 1

Issued: 11/04/2003

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ONE STRIKE FILLER

Product code: ONE - ALL SIZES

Use / description of product: No significant hazard.

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9 0SW

ENGLAND

Tel: +44 (0) 113 240 3456

Fax: +44 (0) 113 200 9418

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: 2-(2-BUTOXYETHOXY)ETHANOL 1-10%

CAS: 112-34-5

EINECS: 203-961-6

[Xi] R36

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

Other hazards: Avoid inhalation of dust when sanding

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Avoid inhalation of dust when sanding

Storage conditions: Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: White

Odour: Barely perceptible odour

Evaporation rate: Slow

Solubility in water: Slightly soluble

Viscosity: Highly viscous

Relative density: 0.4

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Protect from frost

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Ingredients: 2-(2-BUTOXYETHOXY)ETHANOL

ORL MUS LD50 6050 mg/kg

ORL RAT LD50 4500 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

SAFETY DATA SHEET

ONE STRIKE FILLER

13. DISPOSAL CONSIDERATIONS

Disposal operations: D1 Tipping above or underground (e.g. landfill, etc.).

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: -

Shipping name: "NOT SUBJECT TO ADR"

IMDG / IMO

UN no: -

IATA / ICAO

UN no: -

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R36: Irritating to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.